19 + 25 FUSI
1 TESTA STICH 80 mm.

MELITREX

CARATTERISTICHE TECNICHE GENERALI

- Platorelli brocciati, piedini e navette in acciaio temperati e rettificati.
- Apparecchiatura elettronica a scheda modulare con comandi di marcia, arresto, ed impulsi, pulsanti di emergenza con dispositivo di spegnimento automatico a protezione del motore e della scheda stessa.
- Lampada rossa segnale arresto macchina.
- Incroci intercambiabili in acciaio.
- Corsa temperata.
- Motore verticale trifase autoventilato.
- Dispositivo automatico per arresto macchina in caso di rottura filo e di esaurimento anima.
- Cambio passo manuale.

BRAIDING MACHINE GENERAL CHARACTERISTICS

- Breached horngears, shuttles and carriers-feet built in temperated and refaced special cast steel.
- Electronic device with 4 pressure-bottons to start, stop, impulse running, emergency botton with automatic putting out dispositive with driving protection.
- Red lamp to signal,machine stop.
- Interchangeable steel crossing-parts.
- Tempered runway.
- Air cooled, triphase vertical motor.
- Automatic device to stop machine at breaking thread or end shuttle.

Fusi a richiesta montati (R 80 Nr.1) o (H 80 Nr.2) con 4 porcellane bianche. - Bobine (Nr.3 H 80 destra 42x110 / Nr.4 H 80 42x110 o 130mm / Nr.5 R 80 42x110 o 130mm).

On demand carriers mounted (R80 Nr.1) or (H80 Nr.2) with 4 white porcelains. - Bobbins (Nr. 3 right H80 ø 42x110 / Nr. 4 H80 42x110 or 130 mm / Nr. 5 R80 ø 42x110 or 130 mm).

OPTIONAL:
Giro sotto macchina con frenatori o codino di porco,tubi su spina più porcellana. - Fusi con quattro porcellane rosa R 80 - H 80. - Protezione CEE 392/89.- Alimentatore per la gomma. - Motore cambio passo elettronico.

CORDE:
Bordino con tondo da ø 2 a ø 6. - Il piatto con larghezza massima da 4 mm a 12 mm. - E' possibi produrre o solo il tondo o solo il piatto. - E' possibile produrre anche elastico piatto o tondo con le dimensioni uguali alla corda.

OPTIONAL:
Under turn with brakesamns or pigtail, tubes on plug with porcelain. - Carriers with 4 pink porcelains R 80 - H 80. - CEE 392/89 protection. - Supply parts for rubber. - Electronic gear change.

ROPES:
Braid with round from ø 2 to ø 6. - Flat with maximum circumference from 4 mm to 12 mm. - Is possible to produce only round or only flat ropes. - Is also possible make flat or round elastic with the same dimension of rope.

MELITREX

Via Don L. Sturzo, 27 - 20033 DESIO (Mi) - Italy
Tel. 0362.302690 - 0362.302681 - Fax. 0362.303855
www. melitrex.com